


Edition	Description of change	Date

24.4	189		<p>Important information Prior to attaching skylight to roof decking</p> <ol style="list-style-type: none"> 1. Place operator switch to the "On" position. 2. Remote / skylight registration must be started within 10 minutes of placing switch in the "On" position. Review quick start guide. 	<p>Information importante Avant l'installation du puits de lumière au tablier de toiture</p> <ol style="list-style-type: none"> 1. Assurer que le mécanisme d'ouverture est allumé. 2. L'enregistrement du puits de lumière/ télécommande doit s'effectuer entre les 10 minutes après l'allumage du mécanisme. Consulter le guide de démarrage rapide. 	<p>Información importante Antes de sujetar el tragaluz al tablero del techo:</p> <ol style="list-style-type: none"> 1. Seleccione la posición "ON" (Encendido) del interruptor del operador. 2. Debe iniciarse el registro del control remoto/ tragaluz dentro de los 10 minutos de activar el interruptor. Consulte la Guía de uso rápida.
		445398-12-12			

NOTES:

1. Material White semi gloss paper; permanent adhesive.
2. 012 yellow background.
3. Verdana 6 bold black and red font as shown.
4. With 0.001 clear lamination.
5. Delivered on roll.

VELUX SKY-PRS				VSS	
450 Old Brickyard Rd., Greenwood, South Carolina 29648				Deck seal on/off label	
Approvals				Commodity drawing	
Checked by/drawn by/date /RC/26.11.2012				Product instructions no.	
Scale 1:1	Unspec. meas. mm	General tolerance ±1	Size B	Category 21	445398
				000	00
				01	01