



**VERTICAL CROSS SECTION**

**HORIZONTAL CROSS SECTION**

**DETAIL 1**

**PRODUCT DIMENSIONS**

METRIC UNITS (MILLIMETERS)										IMPERIAL UNITS (INCHES)									
Size	Rough Opening Width	Outside Frame Width	Finished Framing Width	Sash Aperture Width	Rough Opening Height	Outside Frame Height	Finished Framing Height	Sash Aperture Height	Daylight Area (Sq. Meters)	Size	Rough Opening Width	Outside Frame Width	Finished Framing Width	Sash Aperture Width	Rough Opening Height	Outside Frame Height	Finished Framing Height	Sash Aperture Height	Daylight Area (Sq. Feet)
CK02	562.3	550	520.4	370.8	791	778	744.2	583.3	.22	CK02	22 1/8	21 5/8	20 1/2	14 5/8	31 1/8	30 5/8	29 5/16	22 15/16	2.37
CK04	562.3	550	520.4	370.8	991	980	944.2	783.3	.29	CK04	22 1/8	21 5/8	20 1/2	14 5/8	39	38 1/2	37 3/16	30 13/16	3.12
CK06	562.3	550	520.4	370.8	1191	1180	1144.2	983.3	.37	CK06	22 1/8	21 5/8	20 1/2	14 5/8	46 7/8	46 3/8	45 1/16	38 11/16	3.98
FK04	673	660	630.4	480.8	991	980	944.2	783.3	.38	FK04	26 1/2	26	24 13/16	18 15/16	39	38 1/2	37 3/16	30 13/16	4.09
FK06	673	660	630.4	480.8	1191	1180	1144.2	983.3	.47	FK06	26 1/2	26	24 13/16	18 15/16	46 7/8	46 3/8	45 1/16	38 11/16	5.06
FK08	673	660	630.4	480.8	1411	1400	1364.2	1203.3	.58	FK08	26 1/2	26	24 13/16	18 15/16	55 1/2	55 1/16	53 11/16	47 5/16	6.24
MK04	794.3	780	750.4	600.8	991	980	944.2	783.3	.47	MK04	31 1/4	30 3/4	29 9/16	23 5/8	39	38 1/2	37 3/16	30 13/16	5.06
MK06	794.3	780	750.4	600.8	1191	1180	1144.2	983.3	.59	MK06	31 1/4	30 3/4	29 9/16	23 5/8	46 7/8	46 3/8	45 1/16	38 11/16	6.35
MK08	794.3	780	750.4	600.8	1411	1400	1364.2	1203.3	.72	MK08	31 1/4	30 3/4	29 9/16	23 5/8	55 1/2	55 1/16	53 11/16	47 5/16	7.75
MK10	794.3	780	750.4	600.8	1613	1600	1566.2	1405.3	.84	MK10	31 1/4	30 3/4	29 9/16	23 5/8	63 1/2	63 1/16	61 11/16	55 5/16	9.04
PK06	956.5	942	912.4	762.8	1191	1180	1144.2	983.3	.75	PK06	37 5/8	37 1/8	35 15/16	30 1/16	46 7/8	46 3/8	45 1/16	38 11/16	8.07
PK08	956.5	942	912.4	762.8	1411	1400	1364.2	1203.3	.92	PK08	37 5/8	37 1/8	35 15/16	30 1/16	55 1/2	55 1/16	53 11/16	47 5/16	9.90
PK10	956.5	942	912.4	762.8	1613	1600	1566.2	1405.3	1.07	PK10	37 5/8	37 1/8	35 15/16	30 1/16	63 1/2	63 1/16	61 1/16	55 5/16	11.52
SK06	1153	1140	1110.4	960.8	1191	1180	1144.2	983.3	.95	SK06	45 3/8	44 7/8	43 11/16	37 13/16	46 7/8	46 3/8	45 1/16	38 11/16	10.23
SK08	1153	1140	1110.4	960.8	1411	1400	1364.2	1203.3	1.16	SK08	45 3/8	44 7/8	43 11/16	37 13/16	55 1/2	55 1/16	53 11/16	47 5/16	12.49
UK04	1353	1340	1310.4	1160.8	991	980	944.2	783.3	.91	UK04	53 1/4	52 3/4	51 11/16	45 11/16	39	38 1/2	37 3/16	30 13/16	9.80
UK08	1353	1340	1310.4	1160.8	1411	1400	1364.2	1203.3	1.40	UK08	53 1/4	52 3/4	51 11/16	45 11/16	55 1/2	55 1/16	53 11/16	47 5/16	15.07

**STANDARD GLAZING OPTIONS:**  
 Laminated LowE3 (60R)

**COMPATIBLE FLASHINGS:**  
 • EDL Step flashing  
 • EKL/EKX Combi flashing  
 • EDW Tile flashing  
 • EKW/EKX Combi tile flashing

**NOTES:**  
 1. The ROUGH OPENING and FINISHED FRAMING dimensions are based on perpendicular interior finish material on all four sides and these dimensions will vary depending on the roof construction, the thickness and the design of the interior finish material.

**VELUX**  
 Sky-Global Product Management  
**GGU - Center-Pivot Roof window**

VELUX  
 1418 Evans Pond Road  
 Greenwood, SC 29649  
 1-800-88-VELUX  
 www.VELUXUSA.com